

Technical Manual



01.011.01

**REMOVE AND INSTALL
REAR SPOILER**

STARK FUTURE



SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



TOOLS

- TRX 30
- TRX 45



OPERATION TIME

12 Minutes

REMOVAL



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Remove the spoiler assembly. Refer to:



01.007.01

[Remove and Install spoiler assembly ↗.](#)



NOTE

Place the spoiler assembly on a smooth surface to avoid scratching the surface while working on it.

- 2 Unscrew the 2x rear screws that secure the rear spoiler to the seat assembly.
- 3 Slide the rear spoiler backwards to release it from the spoiler assembly clips.

INSTALLATION



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.



NOTE

Place the spoiler assembly on a smooth surface to avoid scratching the surface while working on it.

- 1 Slide the rear spoiler forwards into the spoiler assembly clips.
- 2 Tighten the rear spoiler screws to the seat base.
- 3 Install the spoiler assembly. Refer to:



01.007.01

[Remove and Install spoiler assembly ↗.](#)

starkfuture.com

ENG 2023-06

Copyright © 2023 Stark Future SL. All rights reserved.
Reproduction, even in part, as well as copying of all kinds,
is permitted only with the express written permission
of the copyright owner.

STARK FUTURE