Technical Manual



02.004.01

REMOVE AND INSTALL
FRONT BREAK ASSEMBLY

STARK FUTURE



SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



TOOLS

- HEX 8
- TRX 45
- TRX 30
- TRX 25



CONSUMABLES

Medium strength thread locker



OPERATION TIME

17 Minutes

REMOVAL



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

1 Remove the front number plate. Refer to:



01.006.01

Remove and Install front number plate 7.

2 Remove the front line bracket. Refer to:



02.011.01

Remove and Install front brake line bracket 7.

3 Remove the front brake caliper. Refer to:



02.005.01

Remove and Install front brake caliper 7.

4 Remove the hand brake master cylinder. Refer to:



02.009.01

Remove and Install hand break master cylinder 7.



NOTE

Beware of falling objects

INSTALLATION



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

1 Install the front brake master cylinder. Refer to:



02.009.01

Remove and Install hand break master cylinder 7.

2 Install the front brake caliper. Refer to:



02.005.01

Remove and Install front brake caliper 7.

3 Install the front line bracket. Refer to:



02.011.01

Remove and Install front brake line bracket 7.

4 Install the front number plate. Refer to:



01.006.01

Remove and Install front number plate 7.



WARNING

Check brake operation before operating the bike.

starkfuture.com

ENG 2023-06

Copyright © 2023 Stark Future SL. All rights reserved.

Reproduction, even in part, as well as copying of all kinds, is permitted only with the express written permission of the copyright owner.

STARK FUTURE