Technical Manual



06.024.01

REMOVE AND INSTALL
THROTTLE

STARK FUTURE



SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



TOOLS

- TRX 30
- TRX 20



OPERATION TIME

10 Minutes

REMOVAL



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

1 Disconnect the handlebar controls. Refer to:



06.030.07

Disconnect and reconnect handlebar controls ↗.

- 2 Remove the control switch wiring rubber strap.
- 3 Carefully pull the wiring out of the triple clamp routing channel.



NOTE

If you feel excessive resistance when pulling the wiring out of the triple clamp, please check that you disconnected the correct plug or the wiring is not stuck.

- 4 Loosen the throttle clamp bolt.
- 5 Slide the throttle out of the handlebar.

INSTALLATION



WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

1 Slide the throttle onto the handlebar.

(i)

NOTE

The bulky side of the throttle housing should be facing up to prevent impacting your knees on a tight turn.

2 Tighten the throttle clamp bolt to 3 Nm.

 $\left(i\right)$

NOTE

Please ensure throttle can operate freely.

3 Fit the cable through the triple clamp routing channel.

4 Connect the handlebar controls. Refer to:



06.030.07

Disconnect and reconnect handlebar controls ↗.

5 Fit the throttle wiring rubber strap to secure it to the handlebar.



WARNING

Turn ON the bike and connect to the Stark phone to check battery status and that the bike is operating normally after disconnecting electronic components.

starkfuture.com

ENG 2023-08

Copyright © 2023 Stark Future SL. All rights reserved.

Reproduction, even in part, as well as copying of all kinds, is permitted only with the express written permission of the copyright owner.

STARK FUTURE