

Technical Manual



**08.022.01**

**REMOVE AND INSTALL FORK**

**STARK FUTURE**




## SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



## TOOLS

- TRX 45
- TRX 25
- ALN 10



## CONSUMABLES

Lithium grease



## OPERATION TIME

25 Minutes

# REMOVAL



## WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.



## NOTE

Steps 1 and 2 are only for the left side fork.

- 1 Remove the front brake line bracket.  
Refer to:



## 02.011.01

Remove and install the front brake line bracket ↗.

- 2 Remove the front brake caliper.  
Refer to:



02.005.01

Remove and install the front brake caliper ↗.

- 3 Remove the front wheel. Refer to:



09.001.01

Remove and install the front wheel ↗.

- 4 Loosen the triple clamp fork bolts, 2x in the upper triple clamp and 2x in the lower triple clamp.



## WARNING

Beware of falling heavy objects. Hold the fork before loosening the last bolt.

- 5 Gently slide the fork downwards until cleared from the lower triple clamp.

# INSTALLATION



## WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Carefully slide the fork upward through the triple clamps.
- 2 Align the height and orientation of the fork with the bleeders towards the front of the bike.



## NOTE

Hold the fork in place until at least one triple clamp bolt is tighten.

- 3 Tighten the triple clamp bolts to the value engraved on the part, 2x on the top triple clamp and 2x on the lower triple clamp.



## NOTE

Steps 4 and 5 are only for the left side fork.

4 Install the brake caliper. Refer to:



02.005.01

Remove and install the front brake caliper ↗.


5 Install the front brake line bracket.  
Refer to:



02.011.01

Remove and install the front brake line bracket ↗.

6 Install the front wheel. Refer to:



09.001.01

Remove and install the front wheel ↗.



**WARNING**

Check brakes operation before operating the bike.

starkfuture.com

ENG 2023-07

Copyright © 2023 Stark Future SL. All rights reserved.  
Reproduction, even in part, as well as copying of all kinds,  
is permitted only with the express written permission  
of the copyright owner.

**STARK FUTURE**